high-caliber, soft-sided shelters

CAMEL EXPEDITIONARY

EXPLORER SERIES
EXPLORER HUB

FEATURES:

SHELTER HIGHLIGHTS

> stand-alone or centralized structure
> lightweight frame
> 16 ft span in each direction
> easy, tool-free setup
> seamless, watertight transitions
> multi-configuration connections
> rugged and durable
> choose your own 4-wall configuration
> full screened wall option

WORKS WITH

> any Expedition shelters
> all of the Explorer system
> Extreme Weather Liner
> Camel HVAC
> other brand RDS
> add-on assets like generators, showers, and monitor brackets

FABRIC

> military-spec blackout
> flame & mold resistant

COLORS

> Desert Tan 459
> custom options

SET-UP & STRIKE TEAM

> **Explorer Hub** (alone)
2 person minimum / 3 preferred
<20 minutes

MADE FOR:

DISASTER RELIEF | HOSPITALITY | FIRST RESPONDERS | MILITARY*

The Explorer Hub is the ultimate in standalone or connective flexibility. Choose your own four-wall configurations and expand in each direction in 16-foot increments. The entire Explorer Series is designed to grow with your mission with add-ons like generators, HVAC units, lighting, and hygiene or hazmat shower solutions.

**The Expedition Series has not gone through any MIL-Spec testing to be referred to as Military.*

high-caliber, soft-sided shelters

TECH SPECS:

EXPLORER HUB SPECIFICATIONS	
OVERALL DIMENSIONS (LENGTH, WIDTH, HEIGHT)	17 X 17 X 9.5 ft (5.18 X 5.18 X 2.90 m)
USABLE AREA	289 ft² (26.83 m²)
INTERNAL VOLUME	1985 ft³ (56.21 m³)
WITH INSULATION	1775 ft³ (50.26 m³)
SHELTER COMPONENTS	
ECU DUCT PORTS	(8) 14 in (35.56 cm) diameter with elastic sock
DOORWAYS	(4) 48 x 84 in (121.92 x 213.36 cm) double-zippered closure with double-sided hook & loop connection boot
WIND LINE TIE OFF POINTS	(8) frame hard point connections with seatbelt strap
SHELTER AREA	17 x 17 ft (5.18 x 5.18 m) / 289 ft² (26.83 m²)
WIND LOAD	65 mph / gusts 75 mph (104 kmh / gusts 120 kmh)
SNOW LOAD	10 lb / ft² (50 kg / m²)
VINYL	military-spec blackout, NFPA approved flame and mold resistant
DIMENSIONS	
FOOTPRINT | 17 X 17 FT (5.18 X 5.18 m) **SQUARE FOOTPRINT** | 289 ft² (26.83 m²)	
PEAK | 9.50 FT (2.90 m)	
PACKAGED DIMENSIONS AND WEIGHTS IN BAG	
FRAME BAG 1 | 80 x 11 x 11 in (203.20 x 27.94 x 27.94 cm) **WEIGHT** | 100 lb (45.4 kg)	
FRAME BAG 2 | 80 x 11 x 11 in (203.20 x 27.94 x 27.94 cm) **WEIGHT** | 95 lb (43.1 kg)	
FRAME BAG 3 | 34 x 25 x 20 in (86.36 x 63.50 0.81 cm) **WEIGHT** | 150 lb (68 kg)	
PACKAGED DIMENSIONS AND WEIGHTS IN HARD CASES	
HARD CASE 1 | 101.13 x 25 x 24 in (256.86 x 63.50 x 60.96 cm)	
HARD CASE 2 | 50.13 x 25 x 24 in (19.73 x 63.50 x 60.96 cm)	
INDIVIDUAL WEIGHTS	
ROOF | 45 lb (20.4 kg)	**STAKE KIT** | 20 lb (9 kg)
END WALLS | 55 lb (25 kg)	**FRAME ARCHES** | 105 lb (47.6 kg)
FLOOR | 30 lb (13.6 kg)	**FRAME LEG AND ROOF** | 90 lb (40.8 kg)

Camel Expeditionary rapid deployment shelters and products are engineered to give you maximum flexibility. With our uniform connection system, you can build new structures like an entire base camp, medical facility, or expand an existing shelter. All solutions are compatible with previously manufactured Camel Expeditionary models as well as tents from other brands. An award-winning track record and over 100 years success go into every Camel Expeditionary product. We've got you covered, so you can focus on your mission!

INNOVATIVE. EFFICIENT. RELIABLE.

HOW WE'RE MADE.

ASK US ABOUT YOUR SPECIFIC NEEDS FOR RDS!

CAMEL EXPEDITIONARY
+1.423.562.0527
contact@camelexp.com