



CAMEL
EXPEDITIONARY

EXPEDITION 16, 24, 32, & 40 EXPEDITION SERIES SHELTER SYSTEM

FEATURES:



SHELTER HIGHLIGHTS

- > infinitely expandable combinations
- > weather-proof system
- > small footprint, large square footage
- > seamless, watertight transitions
- > multi-entry options
- > rugged and durable



WORKS WITH

- > any Expedition Series shelter
- > Expedition Hub
- > all of the Explorer system
- > Extreme Weather Liner
- > Camel HVAC
- > other brand RDS
- > add-on assets like monitor brackets



FABRIC

- meets U.S. Military guidelines
- > USIFI-PRF-44103
 - > USIFI-PRF-20696

COLORS

- > Camo Green 483
- > Desert Tan 459
- > custom options



SET-UP & STRIKE TEAM

- > **Expedition 16**
2 person minimum / 4 preferred
<10 minutes
- > **Expedition 24**
3 person minimum / 4 preferred
<15 minutes
- > **Expedition 32**
4 person minimum / 6 preferred
<20 minutes
- > **Expedition 40**
6 person minimum / 8 preferred
<25 minutes



100%
MADE IN THE
USA.

MADE FOR: DISASTER RELIEF | LAW ENFORCEMENT | HOSPITALITY | FIRST RESPONDER | MILITARY*

The Expedition Series is an ideal rapid deployable preparedness product for use domestically and abroad. With Expedition options 16, 24, 32, and 40, this series is designed to be connected and grow with your mission.

*The Expedition Series has not gone through any MIL-Spec testing to be referred to as Military.

TECH SPECS:

EXPEDITION SPECIFICATIONS				
MODEL NAME	Expedition 16	Expedition 24	Expedition 32	Expedition 40
EXTERIOR LENGTH	16 ft (4.88 m)	24 ft (7.32 m)	32 ft (9.76 m)	40 ft (12.19 m)
USABLE AREA WITH INSULATION	328 ft ² (30.47 m ²)	492 ft ² (45.71 m ²)	656 ft ² (60.94 m ²)	820 ft ² (76.18 m ²)
ALL EXPEDITION SERIES				
EXTERIOR WIDTH 21.75 ft (6.63 m)				
PEAK HEIGHT 10.00 ft (3.05 m)				
SIDEWALL HEIGHT 6.80 ft (2.07 m)				
DOORS	2	2	2	2
WINDOWS (SIDE WALLS/END WALLS)	4 / 4	6 / 4	8 / 4	10 / 4
ECU DUCTS	4 Sets	4 Sets	4 Sets	6 Sets
STOVE PIPE VENTS	Optional	Optional	Optional	Optional
SNOW AND RAIN LOAD				
SNOW 10 lb/ft ² (4.53 kg/m ²) RAIN 2 in/hr (50.80 mm/hr)				
WIND RATING Sustained winds of 65 mph / 75 mph gusts (104 kmh / 120 kmh)				
TOTAL SYSTEM WEIGHT	485 lb (219.5 kg)	750 lb (340.2 kg)	895 lb (406.0 kg)	1073 lb (486.7 kg)
FRAME SECTION	3 Total	4 Total	5 Total	6 Total
ROOF	1 Total	1 Total	1 Total	1 Total
END WALL	2 Total	2 Total	2 Total	2 Total
SIDEWALL	2 Total	2 Total	2 Total	2 Total
OPTIONAL ITEMS				
LIGHT KITS HARD CASES INSULATION				
BUNK BED CAPACITY	8 (16 People)	12 (24 People)	16 (32 People)	20 (40 People)
COT CAPACITY	8 People	12 People	16 People	20 People



Camel Expeditionary rapid deployment shelters and products are engineered to give you maximum flexibility. With our uniform connection system, you can build new structures like an entire base camp, medical facility, or expand an existing shelter. All solutions are compatible with previously manufactured Camel Expeditionary models as well as tents from other brands. An award-winning track record and over 100 years success go into every Camel Expeditionary product. We've got you covered, so you can focus on your mission!

INNOVATIVE. EFFICIENT. RELIABLE.
HOW WE'RE MADE.
 ASK US ABOUT YOUR SPECIFIC NEEDS FOR RDS!

CAMEL EXPEDITIONARY
 +1.423.562.0527
 contact@camelexp.com